


CAM
EQUIPMENT

TELEPHONE: 01761 434226
FAX No.: 01761 435541
WEB SITE: WWW.CAMequipment.co.uk
E-Mail: Enquiries@CAMequipment.co.uk



FROME HILL, RADSTOCK, Nr BATH, BA3 3PY

MANUFACTURES OF QUALITY GARAGE & WORKSHOP EQUIPMENT SINCE 1972



HEAVY DUTY TRANSMISSION JACKS LOW LEVEL TROLLEY TYPES



FEATURES

- Hydraulic pump is fitted with a automatic relief valve to prevent overload.
- Chrome plated piston rod on ram and pump.
- Smooth hydraulic operation for precise raising and lowering.
- Sensitive lowed lowering by hand operated release.
- Easy manoeuvring and positioning with four heavy duty ball bearing swivel castors with cast-iron wheels, front two castors fitted with directional locks.
- Four fixed handles for ease of precise movement.
- Two position main handle for ease of general movement.

HEAVY DUTY LOW LEVEL **TRANSMISSION JACK**

The CAM range of Transmission Jacks, permits easy one-man transmission removal and replacement.

These units are ideal for handling other assemblies.

the Jack is fitted with four swivel heavy duty Cast-iron wheeled castors. The two front castors are fitted with DIRECTIONAL LOCKS this enables the jack to be moved forward or sideways with ease.

The castors are wide spaced and fitted with ball bearings for exceptional stability and mobility.

The Jack is fitted with a flat plate head adjustable for tilting complete with four adjustable arms to stabilize the unit being removed. The head is complete with a ratchet and web lashing to retain the load onto the lifting head.

The Transmission Jack is fitted with a heavy duty handle for ease of movement. The handle can be locked vertical or in the horizontal position.

There are four fixed handles for the ease of precise sideways adjustment.

The Transmission Jack is fitted with a heavy duty double acting hydraulic pump. The handle can be vertical for ease of pumping outside the vehicle or horizontal when working under a vehicle.

SPECIFICATION

MODEL NUMBER.	CTJ1000	CTJ1500	CTJ2000
CAPACITY	1000 kg	1500 kg	2000kg
LENGTH	1320 mm	1320mm	1320 mm
WIDTH	740 mm	740 mm	740 mm
HEIGHT OF TABLE (Lowered)	235 mm	235 mm	235 mm
WITH STABILIZER FITTED	360 mm	360 mm	360 mm
HEIGHT OF TABLE (Raised)	810 mm	810 mm	810 mm
WITH STABILIZER FITTED	990 mm	990 mm	990 mm
WEIGHT (Approx.)	170 kg	170 kg	170 kg